



## RFWB-20/G & RFWB-40/G - Smart Switch Transmitters



RFWB-20/G




RFWB-40/G

- RFWB-20B: 2-channel (fold) wireless push-button
- RFWB-40B: 4-channel (fold) wireless push-button
- The smart switch transmitters control the various receivers available
- Slimline design with flat mounting surface allowing for easy and quick installation on to most surfaces (glass, wood, wall..)
- The signal is transmitted by wireless communication between system units
- Transmitters can simultaneously operate unlimited number of assigned receivers, which are within range of the transmitted signal
- The range of the signal is dependent on building construction, applied materials and concept of unit location
- Both these smart switches are powered by battery (CR 2032)
- The battery life is approximately 3 to 5 years (depending on frequency of use)

Technical Details	RFWB-20/G	RFWB-40/G
Supply voltage:	3V battery CR 2032	
Transmission indication:	Red LED	
Number of inputs:	2	4
Transmission frequency:	868 MHz	
Type of signal transmission:	Unidirectionally addressed message	
Range in open space:	Up to 200 M'	
Other data		
Operating temperature:	-10 °C to +50 °C ( 14 °F to 122°F)	
Operating position:	Any	
Mounting:	Stick/screw	
Protection degree:	IP20	
Pollution degree:	2	
Dimensions:	94 x 94 x 16 mm	
Weight (without frame):	38 g (1.3 oz.)	39 g (1.4 oz.)
Applicable standards:	EN 60669, EN 300 220, EN 301 489 Directive RTE, NV No.426/2000Sb (Directive 1999/ES)	
Warranty:	12 Months	


RFWB-20/G



Transmission indication

Control buttons

RFWB-40/G



Transmission indication

Control buttons

### Mounting Surfaces

Each smart switch transmitter is supplied with double sided sticky pads so they can be mounted on to most surfaces.

The smart switch transmitters can be fixed to existing back boxes if preferred, screws not supplied.

